



# Endura 210 <sup>210SPS</sup>

## Satin Display Polyester Film

### Applications

- Roller banner displays
- Posters

### Benefits

- Budget roll-up material, white on both sides
- Satin white front polyester surface
- Synthetic photo base alternative with superior smoothness
- Can be grommeted & sewn for cost effective POS solutions

### Post Printing Information for Latex & Solvent Inks:

As with all filmic media, this product must be allowed to “gas-out” after printing.

This can be achieved by leaving the prints face up, ideally 24 hours, to set and harden the unique scratch resistant properties.

If unable to do this e.g. with a long print run, after printing the roll stand it vertically and loosely unwind as much as possible, to allow air in and gases out.

### Recommended Conditions:

Printroom	59°F - 85°F 15°C - 30°C	30% - 65% RH
Usage	50°F - 17°F 10°C - 80°C	10% - 90% RH
Storage	50°F - 68°F 10°C - 20°C	20% - 50% RH

### Printability:

**(Eco) Solvent** ✓✓✓

**Latex** ✓✓✓

**UV** ✓✓✓

### Thickness:

**210** μ **8.3** mil **240** gsm

### Available widths:

**914** 36" **1372** 54"



[www.kernowna.com](http://www.kernowna.com) | [info@kernowna.com](mailto:info@kernowna.com) | (855) 537-6691