



# Opaline Frost 195 195HHF

## Backlit Polyester Film

### Applications

- Lightboxes
- Backlit applications indoor and outdoor
- Frosted binder covers and menu or wine list inserts

### Benefits

- Double diffusion backlight film, printable both sides
- Ideal combination of whiteness and translucency
- Optimum day/night performance
- Scratch and weather resistant for outdoor applications and scrolling displays
- Antistatic treatment avoids attracting dust and slipping in the printer

### Post Printing Information for Latex & Solvent Inks:

As with all filmic media, this product must be allowed to “gas-out” after printing. This can be achieved by leaving the prints face up, ideally 24 hours, to set and harden the unique scratch resistant properties. If unable to do this e.g. with a long print run, after printing the roll stand it vertically and loosely unwind as much as possible, to allow air in and gases out.

### Recommended Conditions:

Printroom	59°F - 86°F 15°C - 30°C	30% - 65% RH
Usage	40°F - 176°F -40°C - 80°C	10% - 90% RH
Storage	50°F - 68°F 10°C - 20°C	20% - 50% RH

Printability:



Thickness:



Available widths:

\*Custom product – please contact your rep for details



[www.kernowna.com](http://www.kernowna.com) | [info@kernowna.com](mailto:info@kernowna.com) | (855) 537-6691

\* from 3<sup>rd</sup> Gen HP or later