



# Ultimate 180 180STL

## Textured Lightblock Roll-Up Polyester Film

### Applications

- Roller banner displays

### Benefits

- Premium roller-banner film - grey back 98% opacity
- Textured, anti-reflective bright-white front surface
- Scratch and water resistant
- No need for lamination
- Antistatic treatment avoids attracting dust and slipping in the printer
- Stiff, perfect flatness

Certified for  
HP Latex Inks

### Post Printing Information for Latex & Solvent Inks:

As with all filmic media, this product must be allowed to “gas-out” after printing. This can be achieved by leaving the prints face up, ideally 24 hours, to set and harden the unique scratch resistant properties. If unable to do this e.g. with a long print run, after printing the roll stand it vertically and loosely unwind as much as possible, to allow air in and gases out.

### Recommended Conditions:

Printroom	59°F - 86°F 15°C - 30°C	30% - 65% RH
Usage	40°F - 176°F -40°C - 80°C	10% - 90% RH
Storage	50°F - 68°F 10°C - 20°C	20% - 50% RH

### Printability:

(Eco) Solvent ✓✓✓

Latex ✓✓✓

UV ✓✓✓

### Thickness:

180 μ 7.1 mil 238 gsm

### Available widths:

914 36" 1067 42" 1270 50"



www.kernowna.com | info@kernowna.com | (855) 537-6691