

Interiors 620

Ultra-resistant non-woven printable wallcoverings

Applications

Customised wallcoverings for very tough environments including POS, retail stores, hotel corridors, schools, offices and hospitals

Benefits

- Easy and fast application - paste the wall not the wallcovering
- Removable dry - without residues or damage to the walls
- Perfect dimensional stability - zero shrinkage for perfect seams
- Washable using mild soap and a sponge or cloth
- Breathable and Bio-Pruf®: inhibits the growth of micro-organisms such as bacteria and mould
- Non-woven substrate with top-coated vinyl
- Fire rated: ASTM Test-Method E84 - 15a
- Certified to work with ClearShield Wall Armor for additional stain, scratch and abrasion resistance
- Check the sample card for the two standard and eight on-demand embossing patterns

Please read the installation instruction before applying

Certified for
HP Latex Inks



Marabu



Post Printing Information for Solvent Inks:

As with all filmic media, this product must be allowed to "gas-out" after solvent printing. This can be achieved by leaving the prints face up, ideally 24 hours. If unable to do this e.g. with a long print run, after printing the roll stand it vertically and loosely unwind as much as possible, to allow air in and solvent out.

Recommended Conditions:

Printroom	15°C - 30°C	30% - 65% RH
Usage	-40°C - 80°C	10% - 90% RH
Storage	10°C - 20°C	20% - 50% RH

Printability:



Thickness:



Available widths:



www.kernowna.com | info@kernowna.com | (855) 537-6691