



Supreme 500 500STVL

Textured Lightblock Pop-Up Polyester Composite Film

Applications

- Pop-up displays

Benefits

- Unbeatable price-quality ratio - grey back 98% opacity
- Lightly textured surface
- Suitable for indoor and outdoor use
- Scratch resistant, no need for lamination
- Antistatic treatment avoids attracting dust and slipping in the printer
- Stiff, perfect flatness

Certified for
HP Latex Inks

Post Printing Information for Latex & Solvent Inks:

As with all filmic media, this product must be allowed to “gas-out” after printing. This can be achieved by leaving the prints face up, ideally 24 hours, to set and harden the unique scratch resistant properties. If unable to do this e.g. with a long print run, after printing the roll stand it vertically and loosely unwind as much as possible, to allow air in and gases out.

Recommended Conditions:

Printroom	59°F - 86°F 15°C - 30°C	30% - 65% RH
Usage	40°F - 176°F -40°C - 80°C	10% - 90% RH
Storage	50°F - 68°F 10°C - 20°C	20% - 50% RH

Printability:

(Eco) Solvent ✓✓✓

Latex ✓✓✓

UV ✓✓✓

Thickness:

495 μ 19.5 mil 660 gsm

Available widths:

914 36" 1067 42" 1270 50"

1524 60"



www.kernowna.com | info@kernowna.com | (855) 537-6691