



FloorShark® 170TFG

Textured Floor Graphic Polyester Film

Applications

- Indoor floor graphic displays
- Supermarkets, shopping malls, convention centers, airports
- All smooth hard floors e.g. concrete & tiling
- Low Pile Carpet tiles

Certified for
HP Latex Inks

Benefits

- Unique sharkskin coating absorbs the ink & dries tough; eliminates the need to laminate
- Sharkskin structure gives great color gamut and high grip
- R10 certificated
- Easy to apply & easy to remove, does not tear into small pieces when removing
- No shrinkage - no risk of a rim of dirty adhesive forming around the print
- Ultra-tough polyester base, resists tearing, resists pallet trucks & stiletto heels

Post Printing Information for Latex & Solvent Inks:

As with all filmic media, this product must be allowed to “gas-out” after printing. This can be achieved by leaving the prints face up, ideally 24 hours, to set and harden the unique scratch resistant properties. If unable to do this e.g. with a long print run, after printing the roll stand it vertically and loosely unwind as much as possible, to allow air in and gases out.

Recommended Conditions:

Printroom	59°F - 85°F 15°C - 30°C	30% - 65% RH
Usage	-40°F - 176°F -40°C - 80°C	10% - 90% RH
Storage	50°F - 68°F 10°C - 20°C	20% - 50% RH

Printability:



Thickness (Total):




Thickness (Face):



Adhesion:



Available widths:



www.kernowna.com | info@kernowna.com | (855) 537-6691